The Texas A&M University System

ORGANIZATION DEPARTMENT AM02 - Texas A&M University Department Organization 401 Joe Routt Boulevard Bill-to-Address 750 Agronomy Road - Suite 3101 Address College Station, TX 77843 **6000 TAMU** Attn: Email invoices to invoices@tamu.edu Attn: Do not mail invoice if sending via email College Station, TX 778436000 Purchaser Angel Constancio Ship-to-Address BSBE BLDG. Room 101 Info Contact Contact JOHNNY FAZZINO at (979)847-9239; 3258 TAMU Email: jfazzino@bio.tamu.edu COLLEGE STATION, TX 77843

BID INFORMATION

Description **Biological Incubator**

Bulletin Desc.

Bid Number AM02-17-B000725 **Bid Opening Date** 11/01/2016 2:00 PM Bid Type Open Market Type Code Invitation for Bid Alternate Id 2017

29008AF Fiscal Year

Pre-Bid Conference

Attachments Bid Information - Bid B000725.pdf

> Substitute W9 - New - February 19 2016~36.pdf Terms and Condtions (NEW) - All Departments~45.pdf

AMENDMENTS

Amendment No. **Amendment Date Amendment Notes**

10/31/2016 1:03 PM Header 1. Bid Opening Date changed from "11/02/2016 02:00:00 PM" to "11/01/2016 02:00:00

Available Date

10/26/2016 4:19 PM

ITEMS					
<u>ltem</u>	<u>Description</u>	Quantity	<u>Unit</u>	Unit Price	<u>Total</u>
1.000	Biological Incubator Model I-36VL, with:	2.00	EA		

- -IntellusUltra Control System for temperature and photoperiod
- -Single-board solid-state design, backward compatible with all Intellus' systems
- -Durable 10-key kindustrial keypad with VFD display and LED indicators
- -3 programming styles: Diurnal, 24 hour, Non-24 hour (elapsed time)
- -Programs can be run in ramping or non-ramping modes
- -Multiple programs may be linked to simulate natural conditions
- -Up to 23 output channels for programmable events
- -Dual experiment protection via primary and independent secondary limits
- -22 guage electro-zinc plated steel exterior and interior, all seams and joints welded
- -Painted with highly reflective white baked enamel
- -Temperature range: 4 degree to 44 degree C (+/- 0.5 degree C) lights ON: 2 degree to 44 degree C (+/- 0.5 degree C) lights OFF
- 1/4 HP continuous running condensing unit
- Top mounted refrigeration for easy access and cleaning
- -29.6 ft capacity
- -Four 32W vertical fluorescent lamps mounted in pairs for light intensity up to 80 micromoles/m2/s
- -Five adjustable shelves for a working area of 23.5 ft2 (2.2m2)
- -One 1" (2.54 cm) Access Port
- -Caster assembly with levelers
- -Electrical requirements: Standard chamber is 115/1/60

The Texas A&M University System

<u>Item Description</u> <u>Quantity Unit Unit Price Total</u>

equipment must be fully insured against loss and damage during shipping.